



Specification

System Parameters

Processor:	High-Performance Embedded SOC Processor
Operation System:	Embedded Linux Operation System

Video Parameters

Camera:	CMOS Low Illumination 1.3 MP HD Colorful Camera
Video Compression Standard:	H.264
Resolution:	1280 x 720
Video frame rate:	25 fps

Audio Parameters

Audio Input:	Built-in Omnidirectional Microphone
Audio Output:	Built-in Loudspeaker
Audio Compression Standard:	G.711 U
Audio Compression Rate:	64 Kbps
Audio Quality:	Noise Suppression and Echo Cancellation

Network Parameters

Ethernet:	10/100 Mbps Self-Adaptive Ethernet
Network Protocol:	TCP/IP, RTSP

Access Control Parameters

Internal Card Reader:	Built-in IC Card Reader
Exit button:	Exit Button for Opening the Door
Door Magnetic Detection:	Detects Door Magnetic Status

Light Supplement

Light Supplement Mode:

IR Supplement

Alarm Parameters

Alarm Input:

Door Magnetic Alarm, Tampering Alarm

Device Interfaces

Network Interface:

1 RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface

RS-485:

1 RS-485 Half-Duplex Port

I/O Input:

4

I/O Output:

1

General

Indoor Station
Access Amount:

4

Material:

Aluminum Alloy

Power Supply:

12 VDC/24 VDC, Power Over Network Cable (DS-KAD606, DS-KAD612)

Power
Consumption:

12 W

Certification: