



Feature

Key Features

1/2.8" progressive scan CMOS

Up to 1920 × 1080@60fps resolution

Min. illumination: Color: 0.005 Lux @(F 1.6, AGC ON) B/W: 0.001 Lux @(F 1.6, AGC ON) 0 Lux with I R

32× optical zoom, 16× digital zoom

WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus

Up to 150 m I R distance

24 VAC & Hi- PoE

Support H.265+/H.265 video compression

Specification

2.1MP, Full HD 1080P

• 1/2.8" CMOS • 0.005Lux@F1.6 Ultra Low Light

- 1920x1080@60fps
- 4.8 - 153mm, 32x Optical Zoom, Auto Focus
- H.265/H.265+/H.264/H.264+ • IR LEDs up to 492ft, Auto Intensity Adjustment
- Smart Tracking, -15° to 90°(Auto-flip)
- True WDR 120dB, 3D DNR, HLC, BLC, Defog, EIS
- Audio I/O, Alarm I/O
- Micro SD Card Slot up to 256GB, ANR
- IP66, Lightning Protection, Surge Protection
- AC 24V, High PoE Max 40W, 7" ()
- AC24V power adapter included • High PoE Injector Sold Separately
- Wall Mount Bracket (DS-1601ZJ) Sold Separately