

Features

- Support H.265/H.264 video formats
- Support TVI,AHD, CVI, CVBS, IP cameras with adaptive access
- 8 channel BNC input
- Up to 8MP resolution for recording
- Support 1-ch HDMI output at up to 4K, 1-ch VGA output at up to 1920*1080
- Long transmission distance over coax cable
- 1TB Harddisk



Specification

Video/Audio Input	
Analog Video Input	8-ch, BNC
IP Video Input	4-ch(only IP up to 12ch)
Supported Analog Camera Types	Support AHD input: 8MP@15fps (channel1-channel2) 5MP@20fps 4MP@30fps 3MP@30fps(channel1 - channel2) 1080P@30fps 720P@60fps Support TVI input: 8MP@15fps(channel1-channel2) 5MP@20fps 4MP@30fps 3MP@20fps (channel1 - channel2) 1080P@30fps 720P@60fps Support CVI input: 8MP@15fps(channel1-channel2) 4MP@30fps 1080P@30fps 720P@60fps Support CVBS input
Audio Input	1-ch, RCA
Two-way Audio	1-ch, RCA
Channel Associated Audio	1-ch,RCA
Network	
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	64Mbps

Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
CVBS Output	1-ch, BNC
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P /960H/4CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	8-ch
Decoding	
Decoding format	H.265/H.264
Live View/ Playback	12MP/8MP/5MP/4MP /3MP/1080P/960P/720P /960H/4CIF/CIF/QCIF
Capability	1 x 4K@30, 1 x 6MP@30, 1 x 5MP@30, 2 x 4MP@30, 2 x 3MP@30, 3 x 3MP@25, 4 x 1080p@30, 8 x 720p@30,
Encoding	
Frame Rate	Main stream: 8MP Lite@8fps(channel1-channel2) 5MP Lite@12fps 4MP Lite@15fps 3MP@15fps(channel1 - channel2) 2MP@15fps 720P@30fps Sub stream: D1@30fps(Max)
Hard Disk	
SATA	2 SATA interfaces
Capacity	Up to 10TB for each HDD
External Interface	
Network Interface	1RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel1 x USB2.0,Front panel1xUSB2.0
Serial Interface	1 x RS485
Alarm In	-
Alarm Out	-
General	

Power Supply	12V DC Power Consumption: 8 W(without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity 90% RH(non-condensing)
Dimensions(W×D×H)	380mm ×315mm× 49mm (15" × 12.4"×1.9")
Weight (without HDD)	<=1.9 Kg (4.19lb)