

Specification

Features

1/2,8" Sony® STARVIS™ CMOS sensor, 4 MP
4X optical zoom
StarLight technology
4MP (2560x1440) at 25 fps
IR range up to 15 meters
Face detection, people counter, perimeter
protection
SMD
WiFi 2,4G and 5G supported
IP66
IK08



Specs

1/2,8" Sony® STARVIS™ CMOS sensor, 4MP
H.265+ / H.265 / H.264+ / H.264 / MJPEG
Digital resolution: 4MP (2560x1440), 3MP
(2048x1536), 1080P (1920x1080), 1,3MP
(1280x960), 720P (1280x720), D1 (704x576), CIF
(352x288)
Stream 1: 4MP, 3MP, 1080P, 1,3MP, 720P (1~25
fps)
Stream 2: D1, CIF (1~25 fps)
Stream 3: 720P , D1, CIF (1~25 fps)
Day/night mode with removable mechanical filter
IR illumination: 3 leds, up to 15 meters
Minimum illumination: 0,005 lux F1.8 (color) /
0,0005 lux F1.8 (B/W), 0 lux IR On

4X optical zoom: 2,8 ~ 12 mm
Viewing angle: 96,9°~31,6°(H), 51,4°~17,8°(V),
116,2°~36,4°(D)
Focus control: auto, semiauto and manual
Automatic Iris Control
16X digital zoom
White balance: Auto, Indoor, Outdoor, Tracking,
Manual, Sodium Lamp, Natural light, light
Gain control: auto and manual
Backlight compensation (BLC, HLC)
WDR true (120 dB)
2D and 3D noise reduction
Digital Defog
EIS
ROI supported
Motion detection supported
Privacy mask supported up to 24 zones and up to
8 zones on the same view
AI:
Count people in the area; generate report
Perimeter protection: Tripwire and intrusion.
Support alarm triggering by target types (human
and vehicle). Support filtering false alarms
caused by animals, rustling leaves, bright lights,
etc.
Face detection supported
SMD supported
IVS:
Event trigger: Motion detection, Video tampering,
Scene changing, Network disconnection, IP
address conflict, Illegal Access, Storage anomaly
General Intelligence: Object Abandoned/Missing
Horizontal positioner: 0° ~ 355°
Vertical positioner: 5° ~ 90°
Manual speed: 0,1° ~ 70°/sec. (H), 0,1° ~
30°/sec. (V)
Preset speed: 80°/sec. (H), 40°/sec. (V)
300 presets
8 rounds (up to 32 presets per round)
Speed adjustment
Audio: 1 in / 1 out

MicroSD card slot up to 256GB (card is not included)

WiFi 2,4G and 5G incorporated

Network interface: RJ45 (10/100 Base-T)

Network protocols: IPv4, IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMPv1/v2c/v3 (MIB-2), DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE, ARP, RTCP

Compatible con ONVIF, CGI

Unicast / Multicast streaming method

Up to 20 users

Remote display with IE, Chrome, Firefox, Safari

Software management Smart PSS, DSS

Compatible with IOS and Android

Power supply: 12V DC /1,5A (3W, 8,5W with IR ON)

Working temperature -30°C ~ +60°C

RH: 95%

IP66

IK08

Lightning-proof 6KV

Metal case

Dimensions: Ø128 x 65,4 mm

Weight: 485 g

Power supply and bracket is included

Features

4M 4x Starlight IR WizSense Network PTZ Camera

- > 1/2.8" 4Megapixel STARVIS™ CMOS
- > Starlight technology
- > Max. 25/30fps@4MP
- > 4x optical zoom
- > Face Detection, People Counting, Perimeter Protection
- > IR distance up to 15m

> WIFI (support 2.4G & 5G)

> SMD Plus

> IP66, IK08

